

RS-SERIES MALE HYDRAULIC COUPLING DATA SHEET¹

Body Material

Nitronic 50 HS

Component Materials	
Poppet Assembly	K500/316 SS
Spring	Elgiloy /Inconel X-750
Spring Seat	316 SS
Spring Seat Retainer	316 SS/Elgiloy
Thrust Washer	Nitronic 60/50 HS
Washer Retaining Clip	Inconel X-750
Retaining Nut	Nit 60/Nit 50 HS/316 SS

Options		
Poppet Seal	PEEK	(-PK)
O-ring	Viton	(-V)
	Chemraz	(-C510)
	HNBR	(-2269)
Poppet	Bleeder	(-B)
	No Poppet	(-NP)

Performance					
Part Series	Pressure Rating		Flow Coefficient (C _v)		
	Delrin Poppet Seal	PEEK Poppet Seal	Standard (200 psi)	High ⁴ Flow	No Poppet
RS-4-A (1/4")	10,000 psi	17,500 psi	.53 ³	1.2	2.6
RS-8-A (1/2")	10,000 psi	15,000 psi	1.9 ²	3.2	6.7
RS-16-A (1")	10,000 psi	15,000 psi	5.5	9.2	16.4

- Notes:
1. Coupling Drawings or Part-Specific Data Sheets take precedence.
 2. C_v = 1.2 when equipped with 800 psi cracking-pressure poppet spring.
 3. C_v = 0.46 when equipped with debris resistant probe.
 4. 200 psi cracking-pressure only. Increased length compared to standard-C_v coupling: RS-4: 1.33" RS-8: 0.63" RS-16: 0.78"

Document Name	Rev.	Created By	Date	Approved By	Date
RS-A DATA	D	JMS	25 JAN 10	CR	27 JAN 10